



CONSPEED HP

PRODUCT CODE : 108

SILICONE BASED HARDENER FOR CONCRETE PAVER BLOCKS

BACKGROUND

ROKSO CONSPEED HP is specially formulated **Silicone based** product. This not only improves quality of the product but reduces highly scarce total time for construction due to very fast setting properties at very low dosage.

ADVANTAGES

- Very low dosage Required
- High initial strength
- Reduced final set time
- Reduced bleeding
- Improved workability
- Fast form work turnaround
- Greater cost effectiveness
- Beneficial when used with fly ash

ROKSO CONSPEED HP primarily reduces the amount of water required to achieve workability. Thus lesser water reduces shrinkage as well as cracking..

DIRECTON FOR USE

Mixing instruction: **ROKSO CONSPEED HP** may be premixed with water in a storage tank or added to concrete along with gauging water with other ingredients of concrete.

DOSAGE

Add **ROKSO CONSPEED HP** in the proportion of Minimum 250 gm to 350 gm per every bag (50kg) of cement. Please note that right dosage can reduce setting time by 2/3^d. PLEASE NOTE THAT ACTUAL DOSAGE SHOULD BE LESSER WHEN TEMPERATURE IS HIGHER & VICE VERSA.

STORAGE

Store in cool place in covered godown.

SHELF LIFE

1 Year from the date of manufacture when store in original packing.

PACKING

Available in User friendly packs of 250 Kgs.

**HIGHLY RECOMMENDED FOR PAVERS ,
SOLID & HOLLOW BLOCKS, AS WELL AS
PRECAST INDUSTRIES**



Manufactured in INDIA by

ROKSO INDIA PRIVATE LIMITED

AN ISO 9001 : 2015 CERTIFIED COMPANY

ADMN.OFFICE : 605,SAI JANAK CLASSIC,ABOVE MURLIDHAR SWEETS, NEAR FLYOVER BRIDGE, DEVIDAS LANE, BORIVALI (W) MUMBAI-92
REGD OFFICE : 202,MADHUVAN,SHRI KRISHNA COMPLEX,NR.SHRIRAM NAGAR,VIVA COLLEGE RD,VIRAR(WEST) DI :PALGHAR -401303 MS
E-MAIL : info@roksoindia.com / WEB SITE : www.roksoindia.com

The data & guidelines provided hereabove is based on compiled information which we believe reliable. Users are requested to test all the applications independently before commercial use. This data & informations are non binding & we donot assure any liability for failure of any guidelines or performance of the product as correct identification of the problem, quality of the other materials & on-site workmanship are factors beyond our control.