



PLASTO BOND HACK AID

PRODUCT CODE : 216

MULTIPURPOSE SURFACE SEALER, PRIMER AND BONDING AGENT.

DESCRIPTION

ROKSO PLASTOBOND is polymer based economical sealer and bonding agent used with cement, for many applications.

PRIMARY USES

- ❖ As an adhesive for most building material.
- ❖ As bonding agent for cement screeds, render and concrete.
- ❖ As bonding agent for hack free plastering.

ADVANTAGES

- ❖ Exceptional bonding properties.
- ❖ Multipurpose application in building industries,
- ❖ Economical and simple to use.

DIRECTION FOR USE

As a bonding agent for cement screeds and rendering, plaster etc: The background must be sound since the adhesion of mortar to the floor, wall or ceiling will only be as good as surface beneath. Carefully examine the surface and remove all flecking and cracking paint, plaster etc. The surface must be stable and sound, thoroughly clean, and free from all oil and grease. Prepare slurry for bond coat as follows:

BOND COAT

1 part **ROKSO PLASTOBOND**, 1 part cement – prepare uniform slurry.
Apply this bond coat on the prepared surface. Apply screed (when using proprietary premixed plasters consult plaster manufacturers recommendations regarding the correct grade to use.)
Cure cementations screeds and renders properly.

BONDING NEW CONCRETE TO OLD TO ELIMINATE COLD JOINTS

Ensure that substrate is sound, thoroughly clean and free from oil, grease and any loosely adhering material. Apply a bond coat of **ROKSO PLASTOBOND** on old concrete and lay the new concrete while this bond coat is tacky. To ensure maximum bond strength add 5 to 7 liters of **ROKSO PLASTOBOND** per 50 kg of cement while concreting.

AS A SURFACE SEALING

To seal highly porous and badly dusting concrete or granolithic sub floors, apply 2 coats of bond coat prepared with **ROKSO PLASTOBOND**. This surface sealer coat has good water resistance.

WATCH POINTS

- ❖ Apply render coat of plaster, new concrete on tacky bond of **ROKSO PLASTOBOND** .
- ❖ If the surface is porous use two coats.
- ❖ Prepare the mix that can be applied within 20 minutes.

COVERAGE

1. FOR 1:1 mix of cement with **ROKSO PLASTOBOND** approximately coverage is 6 sq. Meter.
2. Coverage will increase over unhacked concrete.

PACK SIZE

Available in Userfriendly packs of 20 litre, 50 litre, 100 litre and 210 litre drum.

SHELF LIFE

12 months if stored in original packing.



**Manufactured in INDIA by
ROKSO INDIA PRIVATE LIMITED**

AN ISO 9001 : 2008 CERTIFIED COMPANY

**ADMN.OFFICE: 602,SAI JANAK CLASSIC,ABOVE MURLIDHAR SWEETS, NEAR FLYOVER BRIDGE, DEVIDAS LANE, BORIVALI (W) MUMBAI-92
REGD OFFICE : 202,MADHUVAN,SHRI KRISHNA COMPLEX,NR.SHRIRAM NAGAR,VIVA COLLEGE RD,VIRAR(WEST) DI :PALGHAR -401303 MS
E-MAIL : info@roksoindia.com / WEB SITE : www.roksoindia.com**

The data & guidelines provided hereabove is based on compiled information which we believe reliable. Users are requested to test all the applications independently before commercial use. This data & informations are non binding & we donot assure any liability for failure of any guidelines or performance of the product as correct identification of the problem, quality of the other materials & on-site workmanship are factors beyond our control.