

FIXOBLOCK

PRODUCT CODE : 305

**POLYMER BASED ADHESIVE FOR AAC & CLC BLOCKS
& CONCRETE BLOCKS FIXING
(EUROPEAN GRADE C2)**

DESCRIPTION

ROKSO FIXOBLOCK is a grey powder which consists of blend of portland cements, special cements, polymers and fillers.

ADVANTAGES

No soaking of Block required. Block can go directly from box to the wall minimising breakages during soaking and extra labour.

Surface to be Block need not be made wet as **ROKSO FIXOBLOCK** functions best on dry and clean surfaces. Hence saving in labour.

No curing is required as **ROKSO FIXOBLOCK** paste is self curing type.

Surface to be tiled does not need hacking or mechanical key.

ROKSO FIXOBLOCK waterproof the Block surface.

Excellent adhesion to smooth surface such as existing Block surface etc.

APPLICATION

Mix the powder and water in the volumetric proportion of to 3 volumes of powder to one volume of water. Thoroughly mix to form a creamy paste, leave it for 10 minutes for maturing & apply this paste to the surface to be Block and press the Block in position firmly. An adhesion thickness of 3mm in enough to create a good bond. Allow tiles to set for 24 hours before grouting.

PROPERTIES

Colour	Grey
Compressive Strength	15 N/mm ² in 28days
Fresh wet Density	1.8 -1.90g/cc
Mix proportion by Volume	1 Part Water : 3 Parts of ROKSO FIXOBLOCK
Minimum application Temperature Accommodation	10 C

COVERAGE

On a smooth even surface **ROKSO FIXOBLOCK** gives a coverage of 2.5 square feet per kg. approximately.

SHELF LIFE

12 months if stored in packed condition.

PACKING

ROKSO FIXOBLOCK is supplied in 20 kgs & 40kgs sacks.



**Manufactured in INDIA by
ROKSO INDIA PRIVATE LIMITED**

AN ISO 9001 : 2015 CERTIFIED COMPANY

**ADMN.OFFICE: 605,SAI JANAK CLASSIC,ABOVE MURLIDHAR SWEETS, NEAR FLYOVER BRIDGE, DEVIDAS LANE, BORIVALI (W) MUMBAI-103
REGD OFFICE : 202,MADHUVAN,SHRI KRISHNA COMPLEX,NR.SHRIRAM NAGAR,VIVA COLLEGE RD,VIRAR(WEST) DI :PALGHAR -401303 MS
E-MAIL : info@roksoindia.com / WEB SITE : www.roksoindia.com**

The data & guidelines provided hereabove is based on compiled information which we believe reliable. Users are requested to test all the applications independently before commercial use. This data & informations are non binding & we donot assure any liability for failure of any guidelines or performance of the product as correct identification of the problem, quality of the other materials & on-site workmanship are factors beyond our control.