



## CEMENTITIOUS POLYMER MODIFIED TILE JOINT COMPOUND

### DESCRIPTION

**ROKSO TILE JOINT RANGEEN** is a polymer based cementitious tile joint filler used in filling gaps and levels it self to give hard wearing, non-dusting, tile joints. **ROKSO TILE JOINT RANGEEN** does not allow moisture/water to seep into the back of the tile and cause its dislocation. It firmly holds the tiles together to give a long life to the floor tiles. **ROKSO TILE JOINT RANGEEN** is available in 20 pleasing colours to match the colours of tile (Ask for shade card) **ROKSO TILE JOINT RANGEEN** is recommended of for filling joints upto 6mm width.

### PRIMARY USE

To provide smooth water-resistant hard wearing tile joints.

### TYPICAL APPLICATION

As a tile joint filler in domestic floor and wall tiles of domestic and other commercial establishments, laboratories, bakeries, super markets, showrooms, hospital etc.

### ADVANTAGES

- 1) High Compressive, tensile & flexural strengths ensure carefree joints upto the life of the tile.
- 2) Polymer based
- 3) Waterproof
- 4) Non-dusting
- 5) Easy to use and clean.

### DIRECTION FOR USES

Add 3 to 3½ part **RTJ** to one part of water by volume. Mix to a smooth consistency. let the paste stand for 15 minutes before using.

Apply the paste to the tile joints with a sponge/squeeze trowel. Remove surplus **ROKSO TILE JOINT RANGEEN** with a dumper sponge.

Allow, 24 hours for the filling to dry. Then polish the tile with a clean, dry cloth.

### NOTE:

**ROKSO TILE JOINT RANGEEN** must be filled within 24 hours of fixing the tiles.

### COVERAGE

Depends on the size of the tile and width of the joint, for 3mm deep joints coverage is given in the utility chart below: -



## ROKSO TILE JOINT RANGEEN UTILITY CHART

Approximate Coverage of Tile Grout in square feet per 10kg

TILE SIZE X THINCKNESS(mm)	JOINT WIDTH(mm)						
	3mm	4mm	5mm	6mm	8mm	10mm	12mm
In mm							
100 x 100 x3	480	335	270	225	171	138	116
150 x 150 x4	540	375	301	252	190	153	128
200 x 150 x5	490	342	274	229	173	139	116
200 x 200 x5	570	332	266	267	201	161	135
200 x 300 x6	570	399	319	266	200	161	134
300 x 300 x6	710	496	398	332	249	200	168
400 x 400 x6	950	661	529	442	320	256	214
400 x 450 x7	920	637	510	425	320	256	214
500 x 500 x8	890	619	496	413	310	249	208
600 x 600 x8	1070	737	594	496	372	298	249

### COLOURS

**ROKSO TILE JOINT RANGEEN** is available in 20 pleasing colours.

### STORAGE

Store in damproof covered shade/godown

### SHELF LIFE

12 months from the date of manufacture if stored in original packing.

### PACKAGING

**ROKSO TILE JOINT RANGEEN** is available in 500 gms, 1 kg and 10 kg unit.

Manufactured in INDIA by  
**ROKSO INDIA PRIVATE LIMITED**

AN ISO 9001 : 2015 CERTIFIED COMPANY

ADMN.OFFICE: 605,SAI JANAK CLASSIC,ABOVE MURLIDHAR SWEETS, NEAR FLYOVER BRIDGE, DEVIDAS LANE, BORIVALI (W) MUMBAI-92  
REGD OFFICE : 202,MADHUVAN,SHRI KRISHNA COMPLEX,NR.SHRIRAM NAGAR,VIVA COLLEGE RD,VIRAR(WEST) DI :PALGHAR -401303 MS  
E-MAIL : [info@roksoindia.com](mailto:info@roksoindia.com) / WEB SITE : [www.roksoindia.com](http://www.roksoindia.com)

The data & guidelines provided hereabove is based on compiled information which we believe reliable. Users are requested to test all the applications independently before commercial use. This data & informations are non binding & we donot asure any liability for failure of any guidelines or performance of the product as correct identification of the problem, quality of the other materials & on-site workmanship are factors beyond our control.