



DAMPROOF XP

PRODUCT CODE : 433

HI – PERFORMANCE WATER CASE DAMP PROOF COATING

DESCRIPTION

ROKSO DAMPROOF XP is an optimal blend of high quality acrylic binder, premium grade pigments combined with Rheology Modifiers and Water Proofing Chemicals. This provides excellent Waterproof, tough and flexible decorative and protective coatings.

ADVANTAGES

- ❖ Single Component, ready to use material.
- ❖ Available in any common shades.
- ❖ Can be applied on damp surface
- ❖ Extremely good Waterproof and weather proof,
- ❖ Excellent adhesion, Withstand Expansions, contraction, movements of plastering/concrete surface without deforming, cracking, softening and peeling.
- ❖ Self-Prime System.
- ❖ Resistant to mild acids, detergents and fungus etc.

TYPICAL APPLICATION

- ❖ Ideally suited for applications on plaster bricks, blocks, roughcast plaster blocks.
- ❖ Waterproofing of parapets, outerwalls, chajjas internal and external plastered surface.
- ❖ For sealing hairline cracks and ores on surface
- ❖ For damp patches on the plastered surface of internal wall.

PROPERTIES

Colour	:	Available in all common shades.
Finish	:	Smooth and matt
Speciric	:	1.32
Surface Dry	:	40-60 minutes
Hard Dry	:	4 to 5 hrs
Recommended Coars	:	Minimum two coats.
Coverage	:	70-80 sq.ft./litre/coat.
Film Properties	:	Flexible and tough.
Scratch Hardness	:	Excellent.

PREPARATION OF SURFACES

- ❖ Wire brush and clean all foreign matters such as dirt, grease, laitance, mortar droppings, release agents, efflorescence, loose and flecking materials.
- ❖ Surface to be treated must be sound, firm, and clean. New surface to be cured for minimum 28 days.
- ❖ All large voids or hollow portions must be removed and replastered with **ROKSO CRACKFILLER** and **ROKSO PLASTOCOAT**.
- ❖ Non-moving cracks must be filled with **ROKSO CRACKFILLER**.

METHOD OF APPLICATION

- ❖ Always stir the materials well before use.
- ❖ Apply first coat of **ROKSO DAMPPROOF XP** with the paintbrush directly on prepared surfaces.
- ❖ Allow to dry minimum 4-5 hrs.
- ❖ Apply 2nd coat.

CLEANING OF TOOLS

Wash all containers, brushes, tools and hands with water.

PACKING

ROKSO DAMPPROOF XP available in 1 ltr. & 5 ltr. & 20 ltr. packing.

SHELF LIFE

Minimum one year if stored in cool, dry place and away from direct sunlight in sealed containers.

STORAGE

Store in a cool dry place away from moisture.

Manufactured in INDIA by
ROKSO INDIA PRIVATE LIMITED

AN ISO 9001 : 2008 CERTIFIED COMPANY

ADMN.OFFICE: 602,SAI JANAK CLASSIC,ABOVE MURLIDHAR SWEETS, NEAR FLYOVER BRIDGE, DEVIDAS LANE, BORIVALI (W) MUMBAI-92
REGD OFFICE : 202,MADHUVAN,SHRI KRISHNA COMPLEX,NR.SHRIRAM NAGAR,VIVA COLLEGE RD,VIRAR(WEST) DI :PALGHAR -401303 MS
E-MAIL : info@roksoindia.com / WEB SITE : www.roksoindia.com

The data & guidelines provided hereabove is based on compiled information which we believe reliable. Users are requested to test all the applications independently before commercial use. This data & informations are non binding & we donot assure any liability for failure of any guidelines or performance of the product as correct identification of the problem, quality of the other materials & on-site workmanship are factors beyond our control.