



CONCRETE MUST

PRODUCT CODE : 101

THE ADMIXTURE FOR CONCRETE TO INCREASE WORKABILITY, DURABILITY AND IMPROVED COMPRESSIVE STRENGTH.

BACKGROUND

ROKSO CONCRETE MUST is developed to improve workability of concrete and make it homogenous, **ROKSO CONCRETE MUST** admixed in the concrete at nominal dosage of **140 ml** per bag of cement prevents segregation and bleeding of concrete mix and makes it highly workable without increasing the quantity of water, In hot weather the increased workability allows concrete to be place and compacted for longer time and reduces drying shrinkage and cracking.

ADVANTAGES

- ❖ **Cohesiveness** – with **ROKSO CONCRETE MUST**, the concrete will not segregate.
- ❖ **Workability** – Concrete can be placed easily, rapidly in smaller section with congested reinforcement.
- ❖ **Economical** – In addition to numerous advantages it turns out to be economical. This is because it cuts labour costs lesser cement can used in the concrete for the same workability.
- ❖ **Hot weather concrete** – It acts as coolant and allows placing of concrete in hot climate.
- ❖ **Shrinkage, Cracking and crazing is minimised.**
- ❖ **Durability & weather resistance** – Reduced water demand, reducing capillary permeability of concrete and makes it less susceptible to damage from aggressive environment.

ROKSO CONCRETE MUST primarily reduces the amount of water required to achieve workability. Thus lesser water reduces shrinkage as well as cracking. The admixture also interrupts formation of capillary channels that concrete containing **ROKSO CONCRETE MUST** dose not segregate and remains plastic for a longer period.

DIRECTION FOR USE

Mixing instruction: **ROKSO CONCRETE MUST** may be premixed with water in a storage tank or added to concrete along with gauging water with other ingredients of concrete.

DOSAGE

Add **ROKSO CONCRETE MUST** in the proportion of **140 ml** to every bag (50 Kgs) of cement.

STORAGE

Store in cool place in covered godown.

SHELF LIFE

1 Year from the date of manufacture when store in original packing.

PACKING

Available in User friendly packs of 1 litre, 5 litres, 10 litres, 20 litres, 50 litres. 100 litres and 210 liters. .

Manufactured in INDIA by
ROKSO INDIA PRIVATE LIMITED

AN ISO 9001 : 2015 CERTIFIED COMPANY

ADMN.OFFICE: 605,SAI JANAK CLASSIC,ABOVE MURLIDHAR SWEETS, NEAR FLYOVER BRIDGE, DEVIDAS LANE, BORIVALI (W) MUMBAI-92
REGD OFFICE : 202,MADHUVAN,SHRI KRISHNA COMPLEX,NR.SHRIRAM NAGAR,VIVA COLLEGE RD,VIRAR(WEST) DI :PALGHAR -401303 MS
E-MAIL : info@roksoindia.com / WEB SITE : www.roksoindia.com

The data & guidelines provided hereabove is based on compiled information which we believe reliable. Users are requested to test all the applications independently before commercial use. This data & informations are non binding & we donot assure any liability for failure of any guidelines or performance of the product as correct identification of the problem, quality of the other materials & on-site workmanship are factors beyond our control.