



## **ROKSO STAMPOSEAL PRODUCT CODE : 611**

### **HI - GLOSS CLEAR PROTECTIVE SEALER FOR STAMP CONCRETE**

#### **DESCRIPTION**

**ROKSO STAMPOSEAL EXT** creates a deep penetrating barrier coating which protects and improves surfaces by bringing out richness in the color of Stamp Concrete. It provides a protective barrier on porous surfaces which resists chemical attack and eliminates dusting.

#### **COMPOSITION**

**ROKSO STAMPOSEAL EXT** is a one pack colourless Acrylic resin based coating which provides integral protection to Decorative Stamp Concrete, natural Stones, slates etc.

#### **ADVANTAGES**

**ROKSO STAMPOSEAL EXT** penetrates the capillary structure and provides a tough and clear protection.

**ROKSO STAMPOSEAL EXT** is UV resistant.

**ROKSO STAMPOSEAL EXT** on drying forms a glossy film.

**ROKSO STAMPOSEAL EXT** Coat is free from IMPURITIES

Easy to Apply

#### **TYPICAL APPLICATION**

**ROKSO STAMPOSEAL EXT** can be used for Stamp Concrete and natural stones and slates.

#### **DIRECTION FOR USE**

**ROKSO STAMPOSEAL EXT** can be applied with a hard sponge or a soft brush. One coat will seal, protect and make surface dust free. Additional coats will enhance gloss. Apply second coat after the first coat has dried off.

#### **CAUTION :**

Do not apply **ROKSO STAMPOSEAL EXT** during bad weather or in direct sunlight.

#### **CURING:**

**ROKSO STAMPOSEAL EXT** will dry to tack free within 10 minutes depending upon temperatures and ventilation.

#### **PROPERTIES**

<b>Service Temp :</b>	<b>0°C to 60°C</b>
<b>Flash Point :</b>	Over 25°C.
<b>Specific Gravity :</b>	0.8 at 20°C
<b>Viscosity :</b>	25 seconds on ford cup No.4 @ 20°C

#### **WATCH POINTS**

Ensure adequate ventilation during application.

## COVERAGE

**ROKSO STAMPOSEAL EXT** will give a coverage of approx.100 sq.ft / 1 ltr for single coat. Normally two coats are recommended for Extraordinary Results.

## HEALTH AND SAFETY

**ROKSO STAMPOSEAL EXT** has a low toxicity, but avoid ingestion. Do not induce vomiting if swallowed and seek immediate medical attention. Wear protective gloves during handling and remove splashes on skin with soap water. Wear goggles and in the event of splashes wash eyes with plenty of water for 10-15 minutes. Ensure adequate ventilation. Use of mask and protective eye wear is a must for applicator.

## PACKING AND STORAGE

**ROKSO STAMPOSEAL EXT** is available in 50 ltr & 210 ltr containers.

**ROKSO STAMPOSEAL EXT** can be stored between 10°C and 45°C.

Keep away from sources of ignition and foodstuffs.

## SHELF LIFE

**ROKSO STAMPOSEAL EXT** best results use before 6 months in unopened condition.

## DISCLAIMER

**ROKSO** warrants that all products are free from any defects of manufacture and comply with the specifications given in their respective technical data sheet. No warranty can be given as to the results of use because conditions of use, such as site conditions, surface preparations, workmanship, weather, structural issues and other factors are beyond the control of **ROKSO**. Purchaser agrees to seek the advice of qualified professionals to carry out tests & take trials to determine the suitability of products for their intended purpose prior to full scale usage of **ROKSO** products and assumes all risks.

The company does not assume any liability for unsatisfactory results, arising from the use of our products. Purchaser's sole liability is limited to replacement of product or refund of the purchase price paid if any product proven defective. No other warranties, express or implied, shall apply including any warranty of merchantability or fitness for a particular purpose. **ROKSO** shall not be liable for any consequential damages arising from the use of our products for unsatisfactory results.

**Manufactured in INDIA by**  
**ROKSO INDIA PRIVATE LIMITED**

**AN ISO 9001 : 2015 CERTIFIED COMPANY**

**ADMN.OFFICE: 605,SAI JANAK CLASSIC,ABOVE MURLIDHAR SWEETS, NEAR FLYOVER BRIDGE, DEVIDAS LANE, BORIVALI (W) MUMBAI-92**  
**REGD OFFICE : 202,MADHUVAN,SHRI KRISHNA COMPLEX,NR.SHRIRAM NAGAR,VIVA COLLEGE RD,VIRAR(WEST) DI :PALGHAR -401303 MS**  
**E-MAIL : info@roksoindia.com / WEB SITE : www.roksoindia.com**

The data & guidelines provided hereabove is based on compiled information which we believe reliable. Users are requested to test all the applications independently before commercial use. This data & informations are non binding & we donot assure any liability for failure of any guidelines or performance of the product as correct identification of the problem, quality of the other materials & on-site workmanship are factors beyond our control.